

Toyota Avanza Upper Suction Lock V4.6 Installation Manual

Electric Tailgate Installation

Matters needing attention

- All the pictures in this manual are for reference only. The pictures may be different from the actual objects, but the installation method is the same.
- To facilitate your installation, please carefully read the operation manual of the product before installation; pay attention to protect the surface of your car during installation to avoid scratches.
- Please check regularly that all accessories connected to the car are tight to ensure safe use.

Frequently Asked Questions

Refer to the spare parts list and spare parts drawing to check whether the spare parts are complete. After the installation of the tailgate is completed, raise the tailgate to the desired height, press the switch button on the tailgate, a long "beep" will appear in 3-5 seconds, release the handle, press the tailgate button again, the tailgate will automatically close, let the tailgate close in place, and then a "beep" will appear, that is, the programming of the tailgate is completed.

Installation Steps

1. Remove the original car ball mount of the left upper bracket, and install our ball mount and flat washer (the left and right sides are the same)



2.Remove the original car lower left bracket, install our lower left bracket, and fix it with our screws.



3.Remove the original car lower right bracket, install our lower right bracket, and fix it with our

screws.



4.Remove the original rubber plug. Our hall wire goes through the rubber plug to the tailgate cover

board.



5.Remove the trim panel under the front passenger compartment, unplug the original car fuse, and plug in our power

plug.



6. At the tailgate trim panel, find this screw to connect our grounding

wire



7.Remove the original car lock, install our electric suction, and fix it with the original car

screws.



8. Use the original lock
hook



9 Three-way
plug



10. Find the original opening door car button , install our bracket under the original car, fix it with the original car

screws.



11. Hall wire, central control wire, power cable according to the color are inserted into our control box



12.Fixed position of control box



After the installation is complete, please do the tailgate programming setting. Please make sure that the door can be

closed properly (Move the tailgate to the desired height, press the tailgate switch button, and 3-5 seconds will appear a long beep, release pressed button, press the tailgate button again and the tailgate will close automatically. Let the tailgate close in place, and then there's a "beep" sound, that is, the tailgate programming is completed. **If you do not hear the "beep", the programming is unsuccessful.**

Re-programming; if you can't close the door, use your hand to assist the door to close when you program)

Disclaimer

The related problems and losses caused by improper installation and use are not covered by our company's warranty. Please read this manual carefully before use. Please store carefully after reading, so that you can check it later. The picture is for reference only. The product is subject to the actual object.

Button control mode

1: Long press on tailgate button for three seconds to open or close door on the original car remote control

2: Press once on the open/close door button on the front switch.

Height Setting

Raise the tailgate to the desired height, press the tailgate switch button, 3-5 seconds will appear a "beep" sound, loosen hand, then press the tailgate button to close, the tailgate is closed, and there is a "beep" sound, that is, the tailgate programming is completed

Caution! ! ! Do not manually close the door with your hand after setting the ideal height. Be sure to use our tailgate button.

Electric Tailgate Fault Solution

Fault Phenomenon	Troubleshooting
The original car remote control did not work	Whether the yellow center wire connected properly
Does not work after installation is complete	Check if the positive power supply is connected to 12V-16V Check if the power cord fuse is plugged in. Check if the ground wire is connected
Tailgate do not close properly	Whether the left and right brackets of the poles are reversed Whether the control box cables plugged in properly Whether the bracket is fixed or replaced with our special screw

	<p>There are two vinyls on the left and right sides of the original tailgate. If it is loose, it needs to be tighten.</p>
<p>The original car remote cannot close the door</p>	<p>Whether there is any programming after installation. The first time you install on the car, you need to program by using the tailgate button once.</p> <p>Programming steps; open the door and press and hold the tailgate button for three seconds. When you hear a click, release the hand and press the button again. The tailgate will automatically close and programming is complete.</p>
<p>The tailgate does not go up halfway</p>	<p>Whether the left and right brackets of the poles are reversed</p> <p>Whether the control box cables is plugged in properly</p> <p>Whether the bracket is fixed or replaced with our special screw</p>